



- NOTES: FINISH (PLATING THICKNESS IN MICRO-INCHES)
1. BRASS PER JIS H3250 C3604BD.
  2. P.BRONZE PER JIS H3270 C5441B-H.
  3. NICKEL PL. 100 MIN. OVER COPPER PL. 50 MIN.
  4. GOLD PL. 1-2 MIN. OVER NICKEL PL. 50 MIN. OVER COPPER PL. 50 MIN.
  5. GOLD PL. 3 MIN. OVER NICKEL PL. 50 MIN. OVER COPPER PL. 50 MIN.

NO.	DESCRIPTION	MATERIAL	FINISH	QTY	PART NO.
7	HEX NUT	NOTE 1	NOTE 4	1	SMAA45-5
6	LOCK WASHER	NOTE 1	NOTE 4	1	SMAA45-4
5	FERRULE	NOTE 1	NOTE 3	1	SMAA45CX-081-5
4	INSULATOR	TEFLON		1	SMAA45CX-178-4
3	CONTACT PIN	NOTE 2	NOTE 5	1	SMAA45-316-3
2	INSULATOR	TEFLON		1	SMAA45-316-2
1	BODY	NOTE 1	NOTE 4	1	SMAA45CX-178-1

DIMENSION ARE MILLIMETERS  
UNLESS OTHERWISE SPECIFIED  
TOLERANCES

1-10 = ±0.2  
10-30 = ±0.4  
30-200 = ±1.5  
200-1000 = ±10  
1000-- = ±25

SCALE	REV	UNIT
4 / 1	-	MM

TITLE  
SMA CABLE BULKHEAD  
CRIMP JACK

DRAWING NO.  
SMAA45CX-081

科曼實業有限公司  
**inter-comm enterprise**

CHECKED	DATE
DRAWN	10/30/2012
	10/30/2012

DATE  
10/30/2012